



MyM Pro-3I Micro Master headend

MyM Pro is the ultimate headend solution where ease of use, cost efficiency and performance are essential parameters. The MyM Pro-3I can receive up to 45 Mbit TS (MPTS) via IP, decode the services into analogue format, decrypt if encrypted from source and output 3 analogue channels. Easy installation in 19" rack or on wall (wall mount brackets as accessories).

Simple set up through the embedded web server and Graphical user Interface.

Features:

- 1 input, with ≤ 45 Mbit capacity
- Ethernet (RJ-45 port)
- 3 x MPEG2/MPEG4 decoding, HD-downscaling
- 2 x Common Interface slots for Multi decryption
- 3 x embedded DSB modulators for VHF and UHF with loop through of VHF/UHF/FM. NICAM and A2 stereo
- 3 x A/V output for connection to VSB modulators or for monitoring
- Built in high quality fan for cooling





Technical specification

(This specification may be subject to change without notice).

IPTV Input

Number of inputs	1
Capacity	≤ 45 Mbit, for single MPTS and control
input interface	RJ 45 (same as control) 10/100Base-T/Tx
Input protocol	Multicast, Unicast, UDP, RTP, IGMP v2
Jitter tolerance	+/-100mS packet jitter

3 x MPEG Decoder – Video - audio

Video standard	MPEG2 MP@ML, MPEG4 h.264 AVC
Audio standard	AAC HE or MPEG 1 layer II
Picture aspect ratio	Letterbox, Anamorphic
Teletext	VBI
Subtitling	Teletext or DVB subtitling
Connectors	BNC for video, RCA for audio

3 x Modulator

3 modulators	
Modulation standard	PAL B/G, I, D/K, SECAM
Type of modulation	DSB
Audio	FM-mono, NICAM stereo and A2/A2* stereo
Output channels	Double side band from 160 – 862 MHz.
Output level	Typ. 80 dBμV, fixed
RF output connector	Type F female, 75 Ω

2 x Decryption

Decryption Interface	2 x Common Interface (PCMCIA 5VDC)
Decryption type	Single or Multidecryption CAM's supported

Miscellaneous

AC Power supply	230 VAC typ. (94-264VAC)
AC power consumption	Typ. 18 W
DC output power	12 VDC +/- 10%
DC power consumption	Typ. 15 W
Ethernet port	For set up, software updates and streaming
Set up	Through built in web server
Dimension	383x220x44 mm (excl. connectors)
Weight	2,8 kg
Operating temperature	-20 to +45°C



To view our full line of Professional Products, visit our web site at www.a2b.se.

A2B Electronics AB

P.O. Box 14
SE-591 21 Motala
Sweden

Phone: +46 141 22 91 00
Fax: +46 141 22 91 01
E-mail: market@a2b.se

www.a2b.se

642300.01 rev_A